

KAM35EP_400V

edge banding machine

- touchscreen display
- one-sided automatic edge banding machine with
 - glue tank with heating control and direct glue delivery to straight workpieces
 - crosscut saw unit for cutting the edge band (one unit for front and rear side) 0,37kW motor and 1380min-1 (saw blade speed)
 - double trimming unit for trimming the edge overhang on the workpiece (top/bottom) ; 0,35KW motor per unit and 12000min-1
 - polishing unit (top/bottom) 0,18 kW per unit and 1400min-1
- automatic and constant panel feed thanks to chain conveyor drive and powerful motor
- gluing temperature can be set electronically on the touch display
- edge band support table

Included in delivery: 2x saw blade (ø104xø22x3), 2x polishing disc (ø150mm), 2x cutters for double milling unit



**YOUR
JOB.
OUR
TOOLS.**

KAM35EP_400V

edge banding machine



technical details

motor power s1 in W	3960
feed speed	8 m/min
dust collector port in mm	1 x Ø 50
min. workpiece length in mm	70
min. workpiece thickness in mm	12
edge width in mm	15 - 48
required air pressure in bar	6
gross weight in kg	560
packaging width in mm	645
packaging height in mm	1.235

voltage	400 V / 50 Hz
table height in mm	850
total dimensions in mm	2350 x 1050 x 1320
min. workpiece width in mm	80
max. workpiece thickness in mm	45
edge thickness in mm	0,4 - 3
sound pressure level in dB(A)	78
net weight in kg	495
packaging length in mm	2.000
EAN code	9120132140359

**YOUR
JOB.
OUR
TOOLS.**