

## KAM4EPS\_400V // edge banding machine

- touchscreen display
- one-sided automatic edge banding machine
- glue delivery directly to the workpieces
- unit adjustment equipped with counter for setting different kinds of edges
- milling of the edge overhang (up / down) flush or with 2 mm radius
- accurate cutting of the laminate (back / front) by cutting unit
- straight surface scraping unit
- pressure rollers ensure perfect connection between laminate and workpiece
- automatic and constant panel feed
- adhesive temperature electronically adjustable at the touch panel
- glue tank teflon coated
- integrated dust collection system

**Included in delivery:** machine with 2 x R-scaper blades, saw blades for head-end cutting unit ( $\varnothing$  100 x 30 x 3,2 mm T30), radius cutter ( $\varnothing$ 49 x 20 mm T4), polishing discs ( $\varnothing$ 150 mm)



YOUR  
JOB.  
OUR  
TOOLS.

# KAM4EPS\_400V // edge banding machine



## technical details

motor power s1 in W	6470
feed speed	10 m / min
total dimensions in mm	3960 x 1060 x 1560
min. workpiece width in mm	100
max. workpiece thickness in mm	42
edge thickness in mm	0,4 - 3
weight in kg	855
packaging width in mm	750
packaging height in mm	1550

voltage	400 V / (50-60Hz)
suction port in mm	125
min. workpiece length in mm	100
min. workpiece thickness in mm	8
required air pressure in bar	6-8
sound pressure level in dB(A)	82,9
packaging length in mm	3500
EAN code	9120058379079

YOUR  
JOB.  
OUR  
TOOLS.