

## KAM5EPSV\_400V // edge banding machine

- touchscreen display
- one-sided automatic edge banding machine
- glue delivery directly to the workpieces
- unit adjustment equipped with counter for setting different kinds of edges
- milling of the edge overhang (up / down) flush or with 2 mm radius
- accurate cutting of the laminate (back / front) by cutting unit
- straight surface scraping unit
- pressure rollers ensure perfect connection between laminate and workpiece
- automatic and constant panel feed
- adhesive temperature electronically adjustable at the touch panel
- glue tank teflon coated
- integrated dust collection system
- pre-milling unit with max. 3 mm trimming depth

**Included in delivery:** machine with 2 x R-scaper blades, saw blades for head-end cutting unit (Ø 100 x 30 x 3,2 mm T30), radius cutter (Ø49 x 20 mm T4), polishing discs (Ø150 mm), 2 x pre-milling cutter



YOUR  
JOB.  
OUR  
TOOLS.

# KAM5EPSV\_400V // edge banding machine



## technical details

voltage	400 V / 50-60 Hz	feed speed	10 m/min
motor power s1 in W	9470	suction port in mm	125
min. workpiece length in mm	100	min. workpiece width in mm	100
min. workpiece thickness in mm	8	max. workpiece thickness in mm	42
edge thickness in mm	0,4 - 3 mm	required air pressure in bar	6-8
sound power level in dB(A)	82,9	weight in kg	1090
packaging length in mm	4060	packaging width in mm	785
EAN code	9120058379086	packaging height in mm	1770

YOUR  
JOB.  
OUR  
TOOLS.