

KAM6ALL+_400V // edge banding machine

-
- glue delivery directly to the workpieces
- unit adjustment equipped with counter for setting different kinds of edges
- milling of the edge overhang (up / down) flush or with 2 mm radius
- accurate cutting of the laminate (back / front) by cutting unit
- straight surface scraping unit
- pressure rollers ensure perfect connection between laminate and workpiece
- automatic and constant panel feed
- adhesive temperature electronically adjustable at the touch panel
- glue tank teflon coated
- integrated dust collection system
- pre-milling unit with max. 3 mm trimming depth
- 2 x corner trim-unit for perfect finishing of edge band corners
- Cleaning spray unit helps to clean the edge in front of the polishing unit for a residue-free finishing

Included in delivery: machine with 2 x R-scrapers blades, saw blades for head-end cutting unit (\varnothing 100 x 30 x 3,2 mm T30), radius cutter (\varnothing 49 x 20 mm T4), polishing discs (\varnothing 150 mm), 2 x pre-milling cutter, 2 x corner-trim-milling cutter



YOUR
JOB.
OUR
TOOLS.

KAM6ALL+_400V // edge banding machine



technical details

motor power s1 in W	10570
feed speed	10 m/ min
min. workpiece length in mm	100
min. workpiece thickness in mm	8
edge thickness in mm	0,4 - 3,0
sound power level in dB(A)	82,9
packaging length in mm	5000
EAN code	9120058379093

voltage	400 V / (50-60Hz)
suction port in mm	125
min. workpiece width in mm	100
max. workpiece thickness in mm	42
required air pressure in bar	6-8
weight in kg	1420
packaging width in mm	800
packaging height in mm	1650

YOUR
JOB.
OUR
TOOLS.