

RK1530-CP50-PRO

# ESS MACHINE FISTANCE A

STRUCTURE WITH HIGHEST LEVEL OF RESISTANCE AND RIGIDITY





**1 YEAR WARRANTY** AND UNLIMITED SUPPORT



## TECHNICAL PARAMETERS

Press platen dimensions

Max.total thrust

Pressure of hydraulic system

Max.platen opening

Oil cylinder

Hydraulic motor power

Machine size

Packing size

Weight

1500x3000mm

50T (1.1kg/cm<sup>2</sup>)

210kg/cm<sup>2</sup>

1000mm

125mm x 2pcs, 90mm x 2pcs


4kW

1500x3500x2200mm


1500x3500x2200mm

3000kg

The cold press is the main equipment for the production of cold press veneers for multilayer solid wood composite floors. Compared with the hot presser, the cold presser has a shorter reacting time, using cost is lower.




Suitable for pressing & laminating on fiber boards, decorative papers, plywood & other lamination sheets. Use for various applications for furniture's & board lamination industries.



Mainly use to press various glued wood parts in usual temperature.

Machine has characteristics as good splicing effect & fast high efficiency.



Rigid construction.

Emergency stop switches.



# DETAILS



### **Features:**

### 1.STRUCTURE QUALITY

The sturdy structure has been engineered with a high safety coefficient to guarantee the highest level of resistance and rigidity in each processing phase.

### 2.HYDRAULIC CYLINDERS

The steel rod are electroplated, all gaskets are high resistance to guarantee long lifetime and perfect seal.

### **3.CONTROL PANEL**

For controls and display with digital temperature controllers and adjustable timers for fully automatic cycle



### You Tibe CHECK UP OUR YOUTUBE CHANNEL FOR VIDEO

